



## Carefree®

Floor Sealer/Finish

A versatile floor sealer/finish formulated to work with any maintenance method and equipment on all types of floors

### Versatile

- Works on nearly all types of floors and responds beautifully to conventional, high-speed or UHS equipment and maintenance procedures
- Responds to 175 through 2000 equipment

### Long Lasting Performance

- A sealer and finish easy on, easy off
- Exceptional clarity, high gloss and excellent durability

### *Designed For*

RETAIL

EDUCATION

GOVERNMENT



## Use Overview:

**Carefree® Floor Sealer/Finish** is a versatile product that works on nearly all types of floors and responds beautifully to conventional, high-speed or UHS equipment and maintenance procedures.

### Applying Floor Finish

- Strip floor using JohnsonDiversey stripper according to label instructions.
- Apply 2–4 coats of finish using a clean mop or the **JohnsonDiversey ProSpeed™/MC Finish Applicator System**.
- Apply additional coats if a higher gloss is desired.
- Allow 30 minutes drying time between coats.

### Maintenance

- Dust mop or sweep, clean floor with JohnsonDiversey cleaner following label directions.
- To enhance gloss, spray buff using recommended JohnsonDiversey spray maintainer or with red pad and 175–1500 rpm equipment.
- Dry buff using a white pad and 1000–1500 rpm equipment.
- UHS burnish with a medium to aggressive pad and 2000+ rpm equipment.

### Before Recoating

- Dust mop or sweep, and deep scrub floor using JohnsonDiversey cleaner according to label directions.



- Apply 1 or 2 coats using a clean mop.

### For Best Results

- Do not dilute.
- Do not use on surfaces colder than 10° C (50° F).
- To avoid contamination, do not return unused finish to original container.
- Not intended for use on wood.

**Note:** Floors can be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials.

## Product Specifications:

<b>Color/Form</b>	Milky white liquid
<b>Drying Time</b>	30 minutes (normal conditions)
<b>Non-volatile Solids</b>	20.0%

<b>Shelf Life</b>	2 years
<b>Slip Resistance</b>	0.5 minimum (ASTM D2047)

## Available items:

PRODUCT CODE	DESCRIPTION/PACKAGE SIZE	DILUTION
05432	4 x 1 gallon / 3.78 L Containers	Ready-To-Use
5104731	1 x 5 gallon / 18.9 L Envirobox™/MC	Ready-To-Use
5383021	6 x 2.64 gallon / 2.5 L ProSpeed™/MC BIB (Bag-in-Box)	Ready-To-Use

## Hazard Rating:

HMIS	Concentrate	NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

## Safety Reminder:

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDSs are available on-line at [www.johnsondiversey.com](http://www.johnsondiversey.com) or by calling 1-888-352-2249.

For additional information, please visit:

**800 558 2332 • [www.johnsondiversey.com](http://www.johnsondiversey.com)**