Radiance

High Speed 25

25% Floor Finish



DESCRIPTION

This product is designed for use on all types of resilient flooring in supermarkets, retail, and institutional settings. Gives the ultimate in wet look gloss with superb detergent resistance, and durability. This clear, non-yellowing formula resists dirt penetration to stay looking clean longer. Due to the superior burnish response and repairability, this is the recommended product for floors that will be scrubbed and burnished daily or several times per week.

DIRECTIONS

- 1. Strip floor entirely of old finish using one of our recommended floor strippers.
- 2. Apply finish using a clean finish mop or applicator. Apply 3 7 coats per application. Allow 30 45 minutes after each coat for finish to dry completely before recoating.
- 3. Allow at least 2 hours after final coat dries before burnishing (**NOTE**: It is always recommended to wait 24 hours before burnishing; however, this product can be burnished 2 hours after product dries).
- 4. Maintain floor by dust mopping and spot mopping as needed.
- 5. Auto scrub or damp mop with our recommended floor cleaner using a red pad before burnishing.
- 6. Periodically deep scrub with our recommended floor cleaner and a blue pad before recoating.

FOR USE ON HARD SURFACES SUCH AS CONCRETE, TERRAZZO, MARBLE, OR GRANITE: It is recommended that two coats of sealer be applied to surface to seal floor properly. Follow with 3 - 5 coats of finish. Burnish and maintain as normal.

KEEP FROM FREEZING

APPLICATIONS

Recommended for areas with daily maintenance desired:

- Contract cleaners
- Supermarkets
- Retail

BENEFITS

- High solids--requires fewer coats/ less labor
- Durable
- High off-the-mop gloss
- Easy to maintain
- Will not yellow

SPECIFICATIONS

Color	White
Fragrance	Characteristic
pH Range	8.0 - 8.5
Dilution	RTU
Density	8.65
% Non-Volatile Solids	2 5 %
Coverage	2000 sq. ft./gal.

PACKAGING

ITEM #	SIZE
10079830	5 gal.
10079831	4/1 nal

MADE IN U.S.A. | HECHO EN EEUU.



