

# Radiance

## High Beam 23% Floor Finish



### DESCRIPTION

This product is designed for the professional floor crew that needs a finish that will require fewer coats and still give the high gloss demanded in today's markets. Using a special polymer-resin-wax ratio, it provides superior initial gloss with unsurpassed durability. As few as two coats are needed for most applications. The finish dries to a clear film that will not yellow over time.

### DIRECTIONS

1. Strip floor entirely of old finish using one of our recommended floor strippers.
2. Apply finish using a clean finish mop or applicator. As few as 2 or up to 5 coats may be applied per application. Allow 30 - 45 minutes for finish to dry completely before recoating.
3. Maintain floor by dust mopping and damp mopping as needed.
4. Restore floor by damp mopping thoroughly with our recommended cleaner and buffing (175-2000 rpm) using our recommended spray buff or mop on restorer.

### IF USING THIS PRODUCT ON CONCRETE, TERRAZZO, MARBLE, OR GRANITE:

It is recommended that two coats of sealer be used to seal floor, followed by 2 - 5 coats of finish. Restore and maintain floor as normal.

### RECOMMENDED PADS FOR BUFFING OR BURNISHING:

175-1500 rpm – Soft white or red pad.

1500-2000 rpm – White, champagne, or light natural.

**KEEP FROM FREEZING**

### APPLICATIONS

For areas where stripping or spray buffing can be regularly performed such as:

- Schools and hospitals
- Airports and offices

### BENEFITS

- Non-yellowing
- Saves time and labor
- Highly durable
- Fast drying

### SPECIFICATIONS

Color.....	White
Fragrance.....	Characteristic
pH Range.....	8.0 - 8.5
Dilution.....	RTU
Densi- ty.....	8.60
% Non-volatile solids.....	23%
Coverage.....	2000 sq. ft./gal

### PACKAGING

ITEM #.....	SIZE
10103896.....	5 gal. pail

MADE IN U.S.A. | HECHO EN EEUU.



Distributed by:

# POLLOCK

1 Pollock Place, Grand Prairie, TX 75050  
800.843.7320 • www.pollock.com