Material Safety Data Sheet



STONEMEDIC CIC CERAMIC INTENSIVE CLEANER

1. Product and company identification

Trade name of product : STONEMEDIC CIC CERAMIC INTENSIVE CLEANER

Product use : Floor Cleaner

Product dilution information: Up to 1:1 in water

Supplier's information : Ecolab Inc.

370 N. Wabasha St. St. Paul, MN 55102 1-800-352-5326

Code : 910969-01 **Date of issue** : **01-June-2011**

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

2. Hazards identification

Product AS SOLD

Physical state : Liquid.

Emergency : DANGER!

overview

CAUSES DIGESTIVE TRACT, EYE AND SKIN

BURNS.

CAUSES RESPIRATORY TRACT IRRITATION.

Do not ingest. Do not get in eyes, on skin or on clothing. Avoid breathing vapors, spray or mists. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Potential acute health effects

Product AS SOLD

Eyes : Corrosive to eyes.

Skin : Corrosive to the skin.

Inhalation : Severely irritating to the respiratory system.Ingestion : Causes burns to mouth, throat and stomach.

See toxicological information (section 11)

Product AT USE DILUTION

Liquid. DANGER!

CAUSES DIGESTIVE TRACT, EYE AND

SKIN BURNS.

CAUSES RESPIRATORY TRACT

IRRITATION.

Do not ingest. Do not get in eyes, on skin or on clothing. Avoid breathing vapors, spray or mists. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Product AT USE DILUTION

Corrosive to eyes.
Corrosive to the skin.

Severely irritating to the respiratory system. Causes burns to mouth, throat and stomach.

3. Composition/information on ingredients

Product AS SOLD

<u>Name</u>	CAS number	% by weight
POTASSIUM HYDROXIDE	1310-58-3	4
METHOXYISOPROPANOL	107-98-2	5 - 20
ETHANOLAMINE	141-43-5	1 - 5
BENZYL ALCOHOL	100-51-6	1 - 5
benzene, 1,1'-oxybis-, tetrapropylene derivs., sulfonated, sodium salts	119345-04-9	1 - 5
SODIUM ETHYLHEXYL SULFATE	126-92-1	1 - 5

Product AT USE DILUTION

4. First aid measures

Product AS SOLD

Eye contact

: In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation

: If inhaled, remove to fresh air. If exposed person is not breathing, give artificial respiration or oxygen applied by trained personnel. Get medical attention.

Ingestion

: If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting. Never give anything by quantities of water to drink. Do not induce mouth to an unconscious person. Get medical attention immediately.

Product AT USE DILUTION

In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention immediately.

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Clean shoes thoroughly before reuse.

If inhaled, remove to fresh air. If exposed person is not breathing, give artificial respiration or oxygen applied by trained personnel. Get medical attention.

If material has been swallowed and the exposed person is conscious, give small vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

5. Fire-fighting measures

Product AS SOLD

Hazardous thermal decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide nitrogen oxides sulfur oxides metal oxide/oxides

Fire-fighting media and instructions

: Use an extinguishing agent suitable for the surrounding fire.

Dike area of fire to prevent runoff.

In a fire or if heated, a pressure increase will occur and the container may burst.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Accidental release measures 6.

Personal precautions

Product AS SOLD

: Initiate company's spill response procedures immediately. Keep people out of area. Put on appropriate personal protective equipment (see section 8). Do not touch or walk through spilled

material.

Environmental precautions

: Avoid contact of spilled material and runoff with soil

and surface waterways.

Product AT USE DILUTION

Initiate company's spill response procedures immediately. Keep people out of area. Put on appropriate personal protective equipment (see section 8). Do not touch or walk through spilled material.

Avoid contact of spilled material and runoff with soil and surface waterways.

6. Accidental release measures

Methods for cleaning up

: Follow company's spill procedures. Keep people away from spill. Put on appropriate personal protective equipment (see section 8). Absorb/neutralize liquid material. Use a tool to scoop up solid or absorbed material and put into appropriate labeled container. Use a water rinse for final clean-up.

Follow company's spill procedures. Keep people away from spill. Put on appropriate personal protective equipment (see section 8). Absorb/neutralize liquid material. Use a tool to scoop up solid or absorbed material and put into appropriate labeled container. Use a water rinse for final clean-up.

7. Handling and storage

Product AS SOLD

Handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray. Keep container closed. Use only with adequate ventilation.

Wash thoroughly after handling.

Storage : Keep out of reach of children. Store in a closed

container. Keep container tightly closed.

Store between the following temperatures: -10 and 50°C

Product AT USE DILUTION

Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe vapor or spray. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.

Keep out of reach of children. Store in a closed container. Keep container tightly closed.

Exposure controls/personal protection 8.

Engineering measures

Product AS SOLD

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Personal protection

Eyes

: Use chemical splash goggles. For continued or severe exposure wear a face shield over the goggles.

Hands

: Use chemical-resistant, impervious gloves.

Skin

: Use synthetic apron, other protective equipment as

necessary to prevent skin contact.

Respiratory

: Wear appropriate respirator when ventilation is inadequate and occupational exposure limits are

exceeded.

Product AT USE DILUTION

Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Use chemical splash goggles. For continued or severe exposure wear a face shield over the goggles.

Use chemical-resistant, impervious gloves.

Use synthetic apron, other protective equipment as necessary to prevent skin contact.

Wear appropriate respirator when ventilation is inadequate and occupational exposure limits are exceeded.

Ingredient	Exposure limits	
METHOXYISOPROPANOL	ACGIH TLV (United States, 2/2010). STEL: 553 mg/m³ 15 minute(s). STEL: 150 ppm 15 minute(s). TWA: 369 mg/m³ 8 hour(s). TWA: 100 ppm 8 hour(s). NIOSH REL (United States, 6/2009). TWA: 100 ppm 10 hour(s). TWA: 360 mg/m³ 10 hour(s). STEL: 150 ppm 15 minute(s).	

Exposure controls/personal protection 8.

STEL: 540 mg/m3 15 minute(s). **ETHANOLAMINE**

ACGIH TLV (United States, 2/2010).

STEL: 15 mg/m³ 15 minute(s). STEL: 6 ppm 15 minute(s). TWA: 7.5 mg/m³ 8 hour(s). TWA: 3 ppm 8 hour(s).

OSHA PEL (United States, 6/2010).

TWA: 6 mg/m³ 8 hour(s). TWA: 3 ppm 8 hour(s).

ACGIH TLV (United States, 2/2010). POTASSIUM HYDROXIDE

C: 2 mg/m³

9. Physical and chemical properties

Product AS SOLD

Physical state : Liquid. Flash point : > 100°C Color : Clear

Odor : Alcohol-like

: 13.5 [Conc. (% w/w): 100%] На

Relative density: 1.05

Dispersibility properties

: Easily dispersible in the following materials: cold water

and hot water.

Solubility : Easily soluble in the following materials: cold water

and hot water.

Stability and reactivity 10.

Product AS SOLD

Stability The product is stable. Under normal conditions of storage and use, hazardous

polymerization will not occur.

Reactive or incompatible with the following materials: metals and acids. Reactivity

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

Toxicological information 11.

Potential acute health effects

Product AS SOLD

: Corrosive to eyes. **Eyes** Skin : Corrosive to the skin.

: Severely irritating to the respiratory system. Inhalation Ingestion : Causes burns to mouth, throat and stomach.

Product AT USE DILUTION

Product AT USE DILUTION

Colorless to light yellow [Light]

Liquid.

> 100°C

Alcohol-like

12.5 to 13.5

Corrosive to eyes. Corrosive to the skin.

Severely irritating to the respiratory system. Causes burns to mouth, throat and stomach.

Product AS SOLD Other adverse effects

Target organs : Contains material which causes damage to the following organs: kidneys, liver.

Contains material which may cause damage to the following organs: lungs, upper

respiratory tract, central nervous system (CNS).

12. Ecological information

Ecotoxicity : Not reported

13. Disposal considerations

Product AS SOLD

Waste disposal: Avoid disposal. Attempt to use product completely in

accordance with intended use. Disposal should be in accordance with applicable regional, national and local

laws and regulations.

RCRA: Unused product is D002 (Corrosive)

classification

Product AT USE DILUTION

Avoid disposal. Attempt to use product completely in accordance with intended use. Disposal should be in accordance with applicable regional, national and local laws

and regulations.

14. Transport information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

Product AS SOLD

DOT Classification UN1719

DOT Proper shipping nameCaustic alkali liquids, n.o.s. (Potassium Hydroxide, Monoethanolamine)

Class 8
Packing group III

For transport in bulk or using IMDG regulations, see shipping documents for specific transportation information.

Product AT USE DILUTIONNot intended for transport.

15. Regulatory information

Product AS SOLD

HCS : Corrosive material Classification Target organ effects

Product AS SOLD

U.S. Federal regulations

TSCA 8(b) inventory : All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No listed substance SARA 302/304 emergency planning and notification: No listed substance

SARA 313 Product name CAS number Concentration

Form R - Reporting

requirements

: No listed substance


California Prop. 65 : No listed substance

16. Other information

Corrosive material Target organ effects


16. Other information

Product AS SOLD Hazardous Material : Information System (U.S.A.)



National Fire Protection Association (U.S.A.)





Date of issue : 01-June-2011
Responsible name : Regulatory Affairs
1-800-352-5326

▼ Indicates information that has changed from previously issued version.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.